Sagemcom

XT211-NG

Multi-Energy Electricity Smart Meter
Three-Phase DIN Standard 4 wires



- **Cellular communication LTE Cat M / NB1 / NB2**
- **Automatic Switch Cat M / NB1 / NB2**
- **eSIM MFF2 eUICC**
- **Last Gasp & Neutral current measurement**
- **DLMS Security suite 0 or 1 or 2**
- **Multi-energy: WMBUS 868 MHZ**

SPECIFICATIONS		
Basic Features	**Voltage**	3x220V/380V or 3x230V/400V or 3x240V/415V
	Maximum current	60A or 80A or 100A
	Max switching current per phase	120A
	Frequency	50 Hz ±2%
	Active Energy	EN 50470-3 Class B
	Reactive Energy	IEC 62053-24 Class 2
	Quadrants	Q1 / Q2 / Q3 / Q4, Import / Export Energy
	Real Time Clock	Supercap 7 days or Battery 3 years
	Lifetime	> 20 years
Environment	**Temperature limit range of operation**	-40°C / + 70°C
	Humidity	< 95%
	Protection Index	IP 54
	Fire protection	V-0 (UL94)
Customer Interaction	**Display**	LCD: Dot matrix 5 x 8 Digit Size: 8x3 mm Symbols: 48 (3 lines of 16) Scrolling: auto and manual Backlight: option, remotely configurable
	LEDs	1 for Active Energy 1 for Reactive Energy
	Push Buttons	Main button for scrolling and breaker connection Sealable button for maintenance

MECHANICAL CHARACTERISTICS	
Sealing method: Top cover and bottom cover are sealed together by ultrasonic welding. The terminal block cover is sealed by one dedicated wire-sealable screw.	
Connection diagram	DIN 43856
Mounting	DIN 43857
Cable size	4 – 35 mm²
Terminal Screws	2 screws M6 (Pozidrive) or 1 screw M8 (Pozidrive)
Size (H*W*D)	263*180*90mm (incl. 38mm free space)

INTERFACES		
Integrated communication interfaces	**Maintenance interface**	Optical port (IEC 62056-31)
	HAN customer interface	P1 DSMR 5.0.2 and/or RS485
	Cellular Modem	LTE Cat M / NB1 / NB2 Band 3, 8, 20, 28 Embedded Modem and Internal antenna SMA connector for external antenna
	Multi-energy	SMA connector for WMBUS external antenna
Switches	**Auxiliary Relays**	Up to 2 monostable 5A/230V relays



NB-IoT

LTE-M

IDIS®

Technical features

TIME OF USE

- Programmable Load profiles:
  capture list / capture COSEM objects / capture period
- Programmable Billing profiles:
  capture list / capture COSEM objects / capture period
- Tariff management via built-in programmable output relay
  Calendar/Time of Use management

POWER QUALITY & LTE MONITORING

- Voltage Interruptions (Power down)
- Voltage Restoration (Power Up)
- Neutral loss detection
- Power Supply Quality
- Neutral loss detection
- Last Gasp
- LTE Monitoring Profile

SECURITY, INTEGRITY AND VERIFICATION

- DLMS Security Suite 0 or 1 (ready for Suite 2)
- Auto diagnostic
- Data Storage strategy for integrity
- Local access to the meter by DLMS authentication Password (via the optical port)

FIRMWARE AND LOAD MANAGEMENT

- DLMS / COSEM
- Load Disconnection: locally and remotely
- Local and remote Firmware upgrade

FRAUD DETECTION

- Magnetic field Detection
- Magnetic field immunity
- Neutral current measurement for fraud detection
- Top Cover and Terminal block cover opening/closing detection
- Input - output swap detection
- Phase - Neutral swap detection
- Main power cut detection
- Power factor variation detection

CERTIFICATIONS

- MID Directive 2014/32/EU and the Radio Equipment Directive (RED) 2014/53/EU
- CE Declaration
- LTE CATM / LTE CAT NB2/NB1 (NB-IoT)
- UC3 (breaker) EN 62055-31
- Local/Country Certification on demand

Note: this list of functionalities is not exhaustive. Deeper features list and Security detail can be delivered on special demand under Non-Disclosure Agreement (NDA).

CORE ARCHITECTURE

High speed future proof Cortex™-M4 core microprocessor, integrating crypto/hash processor providing hardware acceleration for AES 128, 192, 256, Triple DES, and hash (MD5, SHA-1) and supporting BSI crypto standard.

All rights reserved. The information and specifications included are subject to change without prior notice. Sagemcom Energy & Telecom tries to ensure that all information in this document is correct, but does not accept liability for error or omission. Non contractual document. All trademarks are registered by their respective owners. Simplified joint stock company - Capital 36.626.034,60 Euros - 518 250 337 RCS Nanterre. 12/2025

Sagemcom Energy & Telecom SAS
Headquarters: 4 allée des Messageries
92271 Bois-Colombes Cedex - FRANCE
Tel : +33 (0)1 57 61 10 00 - Fax : +33 (0)1 57 61 10 01

www.sagemcom.com

Sagemcom